

AMENDMENTS TO THE CLAIMS

1. (Original) An optical cross-connect apparatus, comprising:

a plurality of optical inputs;

a plurality of optical outputs;

an optical cross-connect provided between said plurality of optical inputs and said plurality of optical outputs; and

at least one optical filter provided outside of said cross-connect, said at least one optical filter filtering at least one optical channel of an optical signal flowing into at least one of said plurality of optical inputs or filtering at least one optical channel of an optical signal flowing out of at least one of said plurality of optical outputs or both.

2. (Original) The optical cross-connect apparatus of claim 1, wherein said optical cross-connect includes:

optical splitters optically coupled to said optical inputs; and

optical combiners optically coupled to said optical outputs,

wherein said optical splitters are optically coupled to said optical combiners in a broadcast and combine arrangement.

3. (Original) The optical cross-connect apparatus of claim 2, wherein each optical input is optically coupled to a respective

one of said optical splitters and each optical output is optically coupled to a respective one of said optical combiners.

4. (Original) The optical cross-connect apparatus of claim 1, wherein there are no optical filters included within said optical cross-connect.

5. (Original) The optical cross-connect apparatus of claim 1, wherein the optical cross-connect is spectrally transparent.

6. (Original) The optical cross-connect apparatus of claim 1, wherein at least one of said plurality of optical filters is a multi-band-pass filter.

7. (Original) The optical cross-connect apparatus of claim 1, wherein at least one of said plurality of optical filters is a reconfigurable multi-band-pass filter.

8. (Original) The optical cross-connect apparatus of claim 1, wherein said optical cross-connect includes a plurality of optical couplers.

9. (Original) The optical cross-connect apparatus of claim 1, wherein at least one of said plurality of optical couplers is a passive optical coupler.

10. (Original) A method for cross connecting a plurality of optical inputs and a plurality of optical outputs, the method comprising:

providing an optical cross-connect between the plurality of optical inputs and the plurality of optical outputs; and

optically filtering at least one optical channel of an optical signal flowing into at least one of said plurality of optical inputs or at least one optical channel of an optical signal flowing out of at least one of said plurality of optical outputs or both.

11. (Original) The method of claim 10, wherein the optical cross-connect is spectrally transparent.

12. (Original) The method of claim 10, wherein said optically filtering step includes multi-band-pass filtering at least one optical channel of an optical signal flowing into at least one of said plurality of optical inputs or at least one optical channel of an optical signal flowing out of at least one of said plurality of optical outputs or both.

~~12-~~ 13. (Currently Amended) An optical cross-connect apparatus, comprising:

a plurality of optical inputs;

a plurality of optical outputs;

an optical cross-connect provided between said plurality of optical inputs and said plurality of optical outputs such that paths are formed between a subset of said plurality of optical inputs and a subset of said plurality of optical outputs, wherein a path is defined as a connection between a particular optical input and a particular output; and

at least one optical filter provided outside of said cross-connect such that for at least one path that exists between a particular optical input and a particular optical output, the path's input is filtered or the path's output is filtered or both.

~~13-~~ 14. (Currently Amended) The optical cross-connect apparatus of claim ~~12~~ 13, wherein said optical cross-connect includes:

optical splitters optically coupled to said optical inputs; and

optical combiners optically coupled to said optical outputs,

wherein said optical splitters are optically coupled to said optical combiners in a broadcast and combine arrangement.

~~14.~~ 15. (Currently Amended) The optical cross-connect apparatus of claim ~~13~~ 14, wherein each optical input is optically coupled to a respective one of said optical splitters and each optical output is optically coupled to a respective one of said optical combiners.

~~15.~~ 16. (Currently Amended) The optical cross-connect apparatus of claim ~~12~~ 13, wherein there are no optical filters included within said optical cross-connect.

~~16.~~ 17. (Currently Amended) The optical cross-connect apparatus of claim ~~12~~ 13, wherein for each path, the path's input is filtered or the path's output is filtered or both.

~~17.~~ 18. (Currently Amended) The optical cross connect apparatus of claim ~~12~~ 13, wherein said at least one of said optical filters is a multi-band-pass filter.

~~18.~~ 19. (Currently Amended) The optical cross connect apparatus of claim ~~12~~ 13, wherein said at least one of said input and output optical filters is a reconfigurable multi-band-pass filter.

~~19~~ 20. (Currently Amended) A fiber ring network, comprising:

a first and second outer rings carrying optical signals in a first direction;

a first and second inner rings carrying optical signals in a second direction opposite the first direction; and

an optical cross-connect apparatus as claimed in claim 1 for providing for at least an outer-to-outer connection between the first and second outer rings and an inner-to-inner connection between said first and second inner rings.

~~20~~ 21. (Currently Amended) The fiber ring network of claim ~~19~~ 20, wherein there are no optical filters within said optical cross-connect apparatus, said network further comprising at least one adjacent ring node optically placed in a path of one or more of said first and second outer rings and first and second inner rings such that said adjacent ring node performs an optical filtering function.

~~21~~ 22. (Currently Amended) The fiber ring network of claim ~~20~~ 21, wherein said adjacent ring node includes a multi-band-pass filter.

~~22-~~ 23. (Currently Amended) A mesh network, comprising:  
an optical cross-connect apparatus as claimed in claim 1; and  
an optical add/drop module optically connected to one of said  
plurality of optical inputs and to one of said plurality of optical  
outputs.

~~23-~~ 24. (Currently Amended) The mesh network of claim ~~22~~ 23,  
wherein the optical add/drop module includes a first and second  
multi-band-pass filters.

~~24-~~ 25. (Currently Amended) The mesh network of claim ~~23~~ 24,  
said first and second multi-band-pass filters are optically  
connected to said one of said plurality of optical inputs and to  
said one of the plurality of said optical outputs, respectively.

~~25-~~ 26. (Currently Amended) A method for cross connecting a  
plurality of optical inputs and a plurality of optical outputs, the  
method comprising:

localizing a cross-connecting function of an optical cross-  
connect for cross-connecting the plurality of optical inputs and  
the plurality of optical outputs; and

external optical filtering with reconfigurable optical filter  
external to the optical cross-connect.